

# KARYA DijİTAL

## HIGH PERFORMANCE SOLUTIONS

**M4<sup>26</sup>**

- 216 m<sup>2</sup>/h printing speed
- 260 cm maximum printing width
- Outstanding price/performance ratio for its epon i3200 heads
- n.4 printheads
- Very precise printing, perfectly clear output
- Robust Structure

**Printing Speed**

**216** m<sup>2</sup>/h

**Printing Width**

**260** cm width



**TRU JET**

**TRU PAPER**

**JTEK**

**K//AN**  
DIGITAL

**ergosoft**  
rip solutions

### İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.  
No: 22, Merter - Güngören / İSTANBUL  
T +90 212 637 03 34 | F +90 212 637 03 38

### BURSA

Anadolu Mh. Karlıdağ Sk. No: 37  
Yıldırım - BURSA  
T +90 224 364 61 40 | F +90 224 364 61 46

[www.karyadijital.com](http://www.karyadijital.com)  
[satis@karyadijital.com](mailto:satis@karyadijital.com)

[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital



- Mimimum drop size 2 pl
- n.4 staggered epson i3200 printhead
- n.3200 nozzles per head, n.12800 nozzles in total

- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean




- Pneumatic shafts are used paper feeding & take-up, which can support 500 meters of paper
- Aluminium guide roller with very rigid structure to prevent paper folding

- Independent pump for each print head group
- Independent cleaning pump for wiper & flashing stage.



- Continuous pinch roller design to prevent uneven paper.
- Patented paper suction system with diagonal channels

- Special design patented 2 stage ink feeding system



## TECHICAL PROPERTIES

|                         |   |
|-------------------------|---|
| Print Head              | n.4 On demand Piezo print head / Staggered  |
| Maximum Print Width     | 2750 mm   |
| Ink Type                | Sublimation Dispers   |
| Number of Colors        | 4 Colors, 6-8 Colors (Optional)   |
| Ink Feeding System      | Open bulk system with 20 µm filter.   |
| Media                   | Width: 210 ~ 2750 mm<br>Thickness: 1 mm or less<br>Weight: up to 200 kg<br>Lenght: 400 - 800 m<br>Roll Diameter: 50 mm - 75 mm                  |
| Printing Speeds         | 360 x 1200 dpi - 2 pass 216 m <sup>2</sup> /h<br>360 x 1800 dpi - 3 pass 162 m <sup>2</sup> /h<br>720 x 1200 dpi - 4 pass 108 m <sup>2</sup> /h |
| RIP Software            | ErgoRIP (textprint) / Neostampa / Maintop   |
| Interface               | Gigabit Ethernet  |
| Power Features          | AC 100 ~ 120 V ± 10 / AC 220 ~ 240 V ± 10, 50/60 Hz + 1Hz   |
| Power Consumption       | 300 W or less (except drying unit)  |
| Net Sizes (G x D x Y)   | 4200 x 1100 x 1570mm (G x D x Y)  |
| Gross Sizes (G x D x Y) | 4500 x 1100 x 1200mm (G x D x Y)  |
| Net / Gross Weight      | 750 kg / 930 kg   |