

# KARYA DijİTAL

## HIGH PERFORMANCE SOLUTIONS

# M2

- 75 m<sup>2</sup>/h printing speed
- 190 cm maximum printing width
- Outstanding price/performance ratio for its Epson i3200 heads
- n.2 printheads
- Very precise printing, perfectly clear output
- Robust Structure

**Printing Speed**

**75** m<sup>2</sup>/h

**Printing Width**

**190** cm  
width



**TRU JET**

**TRU PAPER**

**JET**  
TEK  
TEK

**K//AN**  
DIGITAL

**ergosoft**  
rip solutions

### İSTANBUL

Mehmet Nesih Özmen Mh. Savur Sk.  
No: 22, Merter - Güngören / İSTANBUL  
T +90 212 637 03 34 | F +90 212 637 03 38

### BURSA

Anadolu Mh. Karlıdağ Sk. No: 37  
Yıldırım - BURSA  
T +90 224 364 61 40 | F +90 224 364 61 46

[www.karyadijital.com](http://www.karyadijital.com)  
[satis@karyadijital.com](mailto:satis@karyadijital.com)

[f](#) [t](#) [@](#) [v](#) [in](#) /karyadijital



- Mimimum drop size 2 pl
- n.2 staggered Epson i3200 printhead
- n.3200 nozzles per head, n.6400 nozzles in total

- Independent cleaning station for each head
- Flash station which prevents the nozzle clogging in non-used inks & allow the caps to be always clean



- From suction system to dampers, filtration system to electronics, many innovative approach & relative patents

- Independent pump for each print head group
- Independent cleaning pump for wiper & flashing stage



- Continuous pinch roller design to prevent uneven paper
- Patented paper suction system with diagonal channels

- Special design patented 2 stage ink feeding system.



## TECHICAL PROPERTIES

Print Head	n.2 On demand Piezo print head / Staggered
Maximum Print Width	1900 mm
Ink Type	Sublimation Dispers
Number of Colors	4 Colors, 6-8 Colors (Optional)
Ink Feeding System	Open bulk system with 20 µm filter.
Media	Width: 210 ~ 1910 mm Thickness: 1 mm or less Weight: up to 20 kg Lenght: 200 - 300 m Roll Diameter: 50 mm - 75 mm
Printing Speeds	360 x 1200 dpi - 2 pass 75 m <sup>2</sup> /h 360 x 1800 dpi - 3 pass 56 m <sup>2</sup> /h 720 x 1200 dpi - 4 pass 38 m <sup>2</sup> /h
RIP Software	ErgoRIP (textprint) / Neostampa / Maintop
Interface	USB
Power Features	AC 100 ~ 120 V ± 10 / AC 220 ~ 240 V ± 10, 50/60 Hz + 1Hz
Power Consumption	300 W or less (except drying unit)
Net Sizes (G x D x Y)	3130 x 850 x 1440mm (G x D x Y)
Gross Sizes (G x D x Y)	3410 x 830 x 1120mm (G x D x Y)
	335 kg / 480 kg